

Y-TYPE STRAINER



Designed and made as
per
GERMAN Standard

Y-TYPE STRAINER

Technical Specifications

Design standard: DIN 3356

Face to face dimension: DIN 3202

Flanged ends: DIN 2543-2545

Test & inspection: DIN 3230

Connections: Flanged (DIN,ASME), Screwed (BSP,NPT)

Contact us for custom connection types.



Usage

- The DIN Y-Type Strainer effectively removes impurities from the media, safeguarding other equipment and ensuring consistent operation.
- Its stainless steel filter traps offer superior performance and excellent resistance to corrosion.
- Maintenance is straightforward—simply clean the filter traps as needed.



Materials

NO.	Part name	Material
1	Body	GS-C25、GGG-40、1.4401
2	Filter net	1.4301、1.4401
3	Metal gasket	Stainless steel
4	Cover	GS-C25、1.4301、1.4401
5	Nut	ASTM 194-2H、A194-8
6	Double-headed bolt	ASTM 193-B7、A193-B8

Disclaimer: All pictures in this document are a pictorial representation of the product, the actual product may vary.

Y-TYPE STRAINER

PN 16								
DN	Main connection size							
	L	D	D1	D2	b	f	H	n-Φd
15	130	95	65	45	16	2	85	4-Φ14
20	150	105	75	58	18	2	95	4-Φ14
25	160	115	85	68	18	2	110	4-Φ14
32	180	140	100	78	18	2	125	4-Φ18
40	200	150	110	88	18	3	145	4-Φ18
50	230	165	125	102	20	3	155	4-Φ18
65	290	185	145	122	20	3	175	4-Φ18
80	310	200	160	138	20	3	210	8-Φ18
100	350	220	180	158	20	3	230	8-Φ18
125	400	250	210	188	22	3	270	8-Φ18
150	480	285	240	212	22	3	300	8-Φ22
200	600	340	295	268	24	3	385	12-Φ22
250	730	405	355	320	26	3	535	12-Φ26
300	850	460	410	378	28	4	680	12-Φ26

PN 25								
DN	L	D	D1	D2	B	F	H	n-Φd
15	130	95	65	45	16	2	85	4-Φ14
20	150	105	75	58	18	2	95	4-Φ14
25	160	115	85	68	18	2	110	4-Φ14
32	180	140	100	78	18	2	125	4-Φ18
40	200	150	110	88	18	3	145	4-Φ18
50	230	165	125	102	20	3	155	4-Φ18
65	290	185	145	122	22	3	175	8-Φ18
80	310	200	160	138	24	3	210	8-Φ18
100	350	235	190	162	24	3	230	8-Φ22
125	400	270	220	188	26	3	270	8-Φ26
150	480	300	250	218	28	3	300	8-Φ26
200	600	360	310	278	30	3	385	12-Φ26
250	730	425	370	335	32	3	535	12-Φ30
300	850	485	430	395	34	4	680	16-Φ30

PN 40								
DN	L	D	D1	D2	b	f	H	n-Φd
15	130	95	65	45	16	2	85	4-Φ14
20	150	105	75	58	18	2	95	4-Φ14
25	160	115	85	68	18	2	110	4-Φ14
32	160	140	100	68	18	2	125	4-Φ18
40	180	150	110	78	18	3	145	4-Φ18
50	230	165	125	102	20	3	155	4-Φ18
65	290	185	145	122	22	3	175	8-Φ18
80	310	200	160	138	24	3	210	8-Φ18
100	350	235	190	162	24	3	230	8-Φ22
125	400	270	220	188	26	3	270	8-Φ26
150	480	300	250	218	28	3	300	8-Φ26
200	600	375	320	285	34	3	385	12-Φ30
250	730	450	385	345	38	3	535	12-Φ33
300	850	515	450	410	42	4	680	16-Φ33

Contact Us



Ivory Coast

Mr. Rahul

Phone: +225 574654040
EMAIL :- rk@spenomatic.net



Uganda

Mr. Saurabh Patil

Phone: +256706046383
Email :- patil@spenomatic.net



Head Office, Kenya

Mr. Nawzar Zarir Satarawala

Phone: +254 726 729812
Email : nawzar@spenomatic.net



Zambia

Mr. Jaskaran Singh

Phone: +260773579786
Email: jaskaran@spenomatic.net



Tanzania

Mr. Mukul Anand

Phone: +255749502808
Email: mukul@spenomatic.net



Disclaimer: All pictures in this document are a pictorial representation of the product. the actual product may vary. Technical data may vary from the data provided in this document.